TOWN OF LEWISBORO Highway Department

P.O. Box 500 – 11 Main Street South Salem, NY 10590 Tel: (914) 763-3166 Fax: (914) 763-8134

March 6, 2018

Dear Ladies and Gentlemen,

The enclosed specifications are for Highway Materials to be purchased by the Town of Lewisboro through March 31, 2019. The bids will be advertised in the, The Record Review. The opening of bids will be at 10:00 a.m., March 28, 2018 at the Town of Lewisboro Highway Department. Please submit SEALED BIDS to the Highway Department at the above address, and shall bear on the face the name and address of the bidder, bid material, as well as the words SEALED BID. Keep in mind that all submitted bids MUST include your corporate seal, notary signature, and non-collusion bid certificate. Last year's bid results can be found on our web site: www.lewisborogov.com For additional information please call 914-763-3166.

Thank you,

Peter C. Ripperger

Peter C. Ripperger Superintendent of Highways

TOWN OF LEWISBORO NOTICE TO BIDDERS

PLEASE TAKE NOTICE that sealed bids for the purchase of the following materials will be received at the Town of Lewisboro Highway Department, P.O. Box 500, South Salem NY 10590, until 10:00 a.m. on the 28th day of March 2018, at which time they will be opened and publicly read aloud.

The Town of Lewisboro reserves the right to allow all municipal and not for profit organizations authorized under the General Municipal Laws of the State of New York, to purchase any goods and/or services awarded as a result of this bid request in accordance with the latest amendments to NYS GML 100 through 104. However, it is understood that the extension of such contracts are at the discretion of the vendor, and the vendor is only bound to any contract between the Town of Lewisboro and the vendor. Additionally, the Town reserves the right to purchase any goods or services included as part of this bid request from any means legally available to it at any time."

Bituminous Concrete
Bituminous Concrete Laid-in-Place
Liquid Bituminous Materials/Crushed Stone Laid-in-Place
Gravel & Stone
Sand
Catch Basins, Catch Basin Tops, & Grate Risers
Guide Rail & Post Installation
Yellow & White Pavement Marking

Bids MUST be submitted in sealed envelopes to the above address, and shall bear on the face the name and address of the bidder, bid material, as well as the words SEALED BID. Keep in mind that all submitted bids MUST include your corporate seal, notary signature, and non-collusion bid certificate. Specifications, proposal, and bid forms are available at the Highway Department or on our web site: www.lewisborogov.com

The right is reserved to reject any or all bids or to re-advertise for new bids or to accept any bid which is in the best interest of the Town of Lewisboro.

TOWN OF LEWISBORO

PETER RIPPERGER SUPERINTENDENT OF HIGHWAYS

Dated at South Salem, New York this 6th day of March 2018

NON-COLLUSION BID CERTIFICATE

Made pursuant to Section 103-d of the General Municipal law of the State of New York as amended by the Laws of 1966.

By submission of this bid, each bidder and each person signing on behalf of any bidder certifies, and in the case of a joint bid, each party thereto certifies as to his own organization, under penalty of perjury, that to the best of his knowledge and belief:

- 1. The prices in this bid have been arrived at independently without collusion, consultation, communication, or agreement for the purpose of restricting competition, as to any matter relating to such prices with any other bidder or with any competitor. The prices will remain in effect until **March 31, 2019.**
- 2. Unless otherwise required by law, the prices which have been quoted in this bid have not been knowingly disclosed by the bidder and will not knowingly be disclosed by the bidder prior to the opening, directly, or indirectly to any other bidder or to any competitor; and
- 3. No attempt has been made or will be made by the bidder to induce any other person, partnership, or corporation to submit or not to submit a bid for the purpose of restricting competition.
 - a. A bid shall not be considered for award nor shall any award be made where (a) 1, 2, and 3, above, have not been complied with; provided, however, that is in any case the bidder cannot make the foregoing certification, the bidder shall so state and shall furnish with the bid a signed statement which sets forth in detail the reasons therefore. Where (a) 1, 2, and 3, above, have not been complied with, the bid shall not be considered for award nor shall any award be made unless the head of the purchasing unit of the political subdivision, public department, agency or official thereof to which the bid is made, or his designee, determines that such disclosure was not made for the purpose of restricting competition.
- 4. The Town of Lewisboro reserves the right to waive minor informalities, reject any and all Bids, and/or accept the Bid that in its judgment is in the best interest of the Town of Lewisboro.

I hereby affirm under the penalties of perjury that the foregoing statement is true.

State of New York)		Vendor	
County of Westchester)	SS.:	Title	
		, two thousand and eighteen, before me in and who executed the foregoing instrument, are.	
		Notary Public	

BID SPECIFICATIONS FOR LAID-IN-PLACE BITUMINOUS CONCRETE (BLACKTOP)

Price to be on a per ton basis, trucking, paving, and compaction to be included. Pavement preparation, including cleaning and shimming, will be the responsibility of the Town of Lewisboro. The keying of the pavement will be done by the bidder.

Pavement will be laid in accordance with the instructions of the Superintendent of Highways (regarding thickness, width, etc.). Each load will have an individual weigh-master's ticket indicating total tons per load. Tickets will be turned in to the Highway Superintendent's office at the end of each working day. Labor for raking, flagging, and all tasks associated with paving will be supplied by the vendor. This will include feathering and adjustments necessary at both public and private intersections. All surfaces to be tack coated prior to paving.

All bituminous concrete mixes shall be of a uniform nature and in accordance with New York State Department of Transportation Specification, 401-303, dated January 2, 1973, including approved automation and recording of batching all bituminous materials. All aggregates shall be approved as detailed in 401-302 of the fore mentioned State Specifications. Copies of this approval shall be furnished upon request.

Scheduling -- If schedules conflict with the bidder and the Town, the Town reserves the right to use the next lowest bidder in the event the winning bidder cannot in a reasonable period of time fulfill the responsibilities of this bid.

Town of Lewisboro's Superintendent of Highways, or in his absence, the Deputy Superintendent of Highways, shall upon determination that conditions do not exist for good application of material, stop application of materials until conditions improve to his, or her, satisfaction.

Bid must be accompanied by a Non-Collusion Certificate and submitted in a sealed envelope marked: "Bid: Laid-in-Place Blacktop"

Bidder must comply with all New York State labor laws including, but not exclusive of all others, specifically Article 8 (220-223) and Article 9 (230-239) New York State Labor Law. Must comply with New York State Prevailing Wage Law.

The bid must be submitted on the form supplied for this purpose and enclosed with these specifications.

The Town's Superintendent of Highways reserves the right to reject any or all bids and to accept any bid which he deems to be in the best interest of the Town of Lewisboro.

Hauling distance to and from bidder's plant shall be a consideration so as to serve the best interests of the Town of Lewisboro.

The Town of Lewisboro reserves the right to utilize Town forces, equipment rental with operators for paving bituminous concrete, or a combination of same if it is deemed to be in the best interest of the Town of Lewisboro.

BID SPECIFICATIONS FOR LAID-IN-PLACE BITUMINOUS CONCRETE (BLACKTOP)

Mechanical paver to be used by vendor shall have a maximum spread width of twenty (20) feet and no less than ten (10) feet spread width. Compaction shall be provided by a vibratory roller of no less than ten tons compaction ability.

ITEM#	DESCRIPTION	PER NET TON PRICE L-I-P
403.118902 M	Hot Mix Asphalt, Type 1 Base Course	\$
403.138902 M	Hot Mix Asphalt, Type 3 Binder course	\$
403.159802 M		\$
403.139802 W	Hot Mix Asphalt, Type 5 Shim Course	Φ
403.178902 M	Hot Mix Asphalt, Type 6 Top Course	\$
403.178302 M	Hot Mix Asphalt, Type 6F3 Top Course	\$
403.198302 M	Hot Mix Asphalt, Type 7F3 Top Course	\$
403.218902 M	Hot Mix Asphalt, True and Level Course	\$
404.178902	Warm Mix Asphalt, Type 6F3- Top	\$
404.118902	Warm Mix Asphalt, Type 1 Base Course	\$
404.138902	Warm Mix Asphalt, Type 3 Binder	\$
402.098101	9.5mm Super Pave Top	\$
402.128102	12.5mm Super Pave Top	\$
402.198901	19.0mm Super Pave Top	\$
402.258901	25.0mm Super Pave Top Binder	\$
402.378901	37.5mm Super Pave Top Base	\$
402.068101	6.3 Polymer Modified Top	\$

PRICE ADJUSTMENT CLAUSE:

In view of the uncertainty and fluctuation of Asphalt Cement prices, bidder shall use \$461.00 effective March 5, 2018, per ton base average AC-20 material for the purpose of this bid. Price adjustments during the life of this bid shall be made in accordance with that formula and procedure set forth by the New York State Office of General Services.

LAID-IN-PLACE BITUMINOUS CONCRETE (BLACKTOP)

Price adjustment = % of AC - 20 New posted terminal prices – \$461.00 base average Documentation of the price of AC-20 must be submitted with invoice. **Seal of Corporation** Legal name of Firm, Person, or Corporation: **Business Address:** Signature: By:_____ Title:

BID SPECIFICATIONS FOR BITUMINOUS CONCRETE (BLACKTOP) FOB

HOT MIX AND COLD MIX: MIXING METHOD OPTIONAL ALL ITEMS

Price to be on a per ton basis, F.O.B. bidder's plant, loaded into Town vehicles.

All bituminous concrete mixes shall be of uniform nature and in accordance of New York State Department of Transportation Specifications section 401-302, dated January 2, 1973, including approved automation and recording of batching all bituminous materials. All aggregates shall be approved as detailed in Section 401-302 of aforementioned State Specifications. Copies of this approval shall be furnished upon request.

Hauling distance to bidder's plant shall be a consideration so as to serve the best interests of the Town of Lewisboro.

Bid must be accompanied by a non-collusion certificate and submitted in a sealed envelope marked "BID-Blacktop-SEALED BID."

The bid must be submitted on the form supplied for this purpose and attached to these specifications.

The Town Highway Superintendent reserves the right to reject any or all bids and to accept any bid which he deems favorable to the best interests of the Town of Lewisboro.

BID FOR BITUMINOUS CONCRETE (BLACKTOP) FOB

ITEM#	MATERIAL DESCRIPTION	PER NET TON PRICE F.O.B.
403.118902 M	Hot Mix Asphalt, Type 1 Base Course	\$
403.138902 M	Hot Mix Asphalt, Type 3 Binder course	\$
403.159802 M	Hot Mix Asphalt, Type 5 Shim Course	\$
403.178902 M	Hot Mix Asphalt, Type 6 Top Course	\$
403.178302 M	Hot Mix Asphalt, Type 6F3 Top Course	\$
403.218902 M	Hot Mix Asphalt, True and Level Course	\$
714-06	Asphaltic Concrete Curb Mix	\$
403-2001	Winter Mix	\$
Optional	Plant Fine Top Mix	\$

PRICE ADJUSTMENT CLAUSE:

In view of the uncertainty and fluctuation of Asphalt cement prices, bidder shall use \$461.00 effective March 5, 2018 per ton average AC-20 material for purpose of this bid. Price adjustment during the life of this bid shall be made in accordance with that formula and procedure set forth by New York State Office of General Services.

BITUMINOUS CONCRETE (BLACKTOP)

Price adjustment = $\%$ of AC = 20 (New Posted Terminal Price - \$461.00 Base Average Documentation of the price of AC-20 must be submitted with invoice.			
of Lewisboro Highway Garage at South Sal	and is within miles of the Town lem, New York and bidder certifies that all items meet ion Specifications. Distance shall be a consideration.		
Seal of Corporation	Legal name of Firm, Person, or Corporation:		
	Business Address:		
By:	Signature:		
	Title:		

LIQUID BITUMINOUS MATERIALS

All BIDDERS TO QUALIFY MUST CERTIFY THAT:

- 1. Each distributing tank truck doing work in the Town will be manned by two (2) men and the following equipment: Hand-hose, pouring pot, spray bars adjustable over eight (8) feet in one (1) foot increments and two (2) squeegees.
- 2. They have plant for the storage and distribution of bituminous materials with heated storage and have maintained such a plant for a period of at least one year. A Plant is defined, as a site where at least 20,000 gallons storage for each grade of materials required is available with pumping and heating facilities. Trailer trucks and tank cars shall not be considered a plant.
- 3. All materials shall meet the New York State DOT specifications, section 702.

Quantities ordered may be in less than 500-gallon truck amounts and on twelve (12) hours notice. All application of material is to be made under the direction of the Superintendent of Highways or his authorized representative.

Deliveries are to be made where and when as requested by the Superintendent of Highways.

Payment shall be based on the actual number of gallons of materials delivered to the state as certified by receipt.

Bids must be accompanied by a Non-Collusion form and submitted in a sealed envelope marked "BID-Liquid Bituminous Materials-SEALED BID."

TABLE 702-4 ITEM 1 Medium Curing Cutback,	Per Gal Applied
TABLE 702-3 ITEM 2 Rapid Curing Cutback	Per Gal Applied
Table 702-1 ITEM 3 Penetration Asphalt Binder TABLE 702-5 & 702-6	Per Gal Applied
ITEM 4 CRS-2 Cationic Emulsion	Per Gal Applied
ITEM 5 6.3mm Polymer modified	Per Gal Applied
CONTINUED	

BITUMENS & CRUSHED STONE (Complete in Place) (NYS DOT 410-3.01)

The following items shall include the cost of all labor, materials, and equipment necessary to properly apply, distribute and roll the specified Bituminous Materials and 3/8" crushed stone in accordance with Department of Transportation specifications.

The Town highway personnel shall machine sweep the roads prior to the start of work. *All Flagman & Traffic Control shall be supplied by the Bidder*. No materials shall be stockpiled on Town property and the Town will not load any trucks. The Town will sweep the roads 7 to 10 days after placement of Oil & Stone. The contractor must have a self propelled computerized stone spreader of variable width from 8' minimum to 16' maximum.

Payment shall be on the basis of each gallon of liquid bituminous material applied. **ITEM 6,** Rapid Curing Cutback, including 3/8" stone applied & rolled ______ Per Gal **ITEM 7,** Penetration Asphalt Binder including 3/8" stone applied & rolled Per Gal ITEM 8, CRS-2, Emulsified asphalt including 3/8: stone applied & rolled ______ Per Gal Bids must be accompanied by a Non-Collusion form and submitted in a sealed envelope marked "BID-Bitumens & Crushed Stone." **ESCALATION CLAUSE** It shall be agreed by the Town and the bidder that the Bid Unit Price is subject to escalation/deescalation per the formula set forth by the NYS OGS contract in effect at the time of the bid opening. In other words, based on March 5, 2018, posting of \$461.00 per ton of liquid asphalt. **Seal of Corporation** Legal name of Firm, Person, or Corporation: **Business Address:** Signature: _____ By:____

Title:

BID SPECIFICATIONS FOR GRAVEL & STONE

All materials must conform to N.Y.S. Dept. of Transportation specifications.

Material samples must be submitted to the Highway Superintendent upon request prior to bid award.

Bids must be accompanied by a Non-Collusion form and submitted in a sealed envelope marked "BID-Gravel & Stone- SEALED BID."

The successful bidder will be required to enter into a contract with the Town of Lewisboro and agree that the unit price bid is the price at which material will be furnished for the life of the contract and that the materials ordered will be furnished when and as directed.

The Town Superintendent of Highways reserves the right to reject any or all bids and to accept any bids which he deems favorable to the Town of Lewisboro.

Bidder must show mileage from the plant to the Town of Lewisboro Highway Dept. Garage at South Salem New York.

Bidder should specify the bid by the ton.

TOWN OF LEWISBORO BID SPECIFICATIONS FOR GRAVEL & STONE

Crushed Stone		Delivered Dark Gray	Delivered Limestone
703-0201A	Size 1A – 1/4"	per ton	per ton
703-0201B	Size 1 ST – 3/8"	per ton	per ton
703-0201C	Size 1 – 1/2"	per ton	per ton
703-0201D	Size 2 – 3/4"	per ton	per ton
703-0201E	Size 3A – 1 1/2"	per ton	per ton
703-0201F	Size 3 – 2"	per ton	per ton
Stone Fill		Delivered Dark Gray	Delivered Limestone
620.02	Fine Stone Fill	per ton	per ton
620.03	Light Stone Fill	per ton	per ton
620.04	Medium Stone Fill	per ton	per ton
620.05	Heavy Stone Fill	per ton	per ton
Item 4		Delivered	
304.02	Type 1 Sub base Course – Eart	h tone per ton	
	Recycled Item 4	per ton	

Name and location of quarry:	
NYSDOT# for Product Source	
	and is approximately miles from the ent Garage at South Salem, New York. Distance shall
Seal of Corporation	Legal name of Firm, Person, or Corporation:
	Business Address:
By:	Signature:
	Title:

SPECIFICATIONS FOR SAND

Separate bids to be submitted on bid form for price per ton F.O.B. Bidder's plant should be with a radius of 15 miles of the Town of Lewisboro Highway Department sand and salt dome. Mileage is a factor in determining bid award for both F.O.B. and delivered.

A sample of material will be supplied to the Superintendent of highways upon request.

The successful bidder agrees through his bid to supply the same material at the same unit price through that period of time.

The Superintendent reserves the right to reject any and or all bids and to accept those bids he considers to be the most favorable to the best interests of the Town of Lewisboro.

Bids must be accompanied by a Non-Collusion form in a sealed envelope and marked "BID-Sand- SEALED BID." Bids must be submitted on the form supplied and attached to these specifications.

BID FOR SAND

FOB Per	Ton		
	ICE CONTROL SAND	per ton	
	DRY SCREENED	per ton	
Delivered	Per Ton		
	ICE CONTROL SAND	per ton	
	DRY SCREENED	per ton	
	vn of Lewisboro Highway Gara	and is within miles ge at South Salem, New York. Distance shall be a	S
Seal of Co	orporation	Legal name of Firm, Person, or Corporation:	
		Business Address:	
Ву:		Signature: Title:	

BID SPECIFICATIONS CATCH BASINS AND CATCH BASIN TOPS

1. FORM OF BID

Bid must be submitted in a sealed envelope and marked "BID-Catch Basins- SEALED BID." Each bid must include a signed certificate of Non-Collusion and waiver of immunity as required by law.

Bid is not to include taxes from which the Town of Lewisboro is exempt by law. Tax exemption certificate #146002276 covers Highway purchases by the Town of Lewisboro.

Price of bid shall be for equipment delivered to the Town of Lewisboro Highway Garage, South Salem, New York, 10590.

2. EXCEPTIONS TO SPECIFICATIONS

If the equipment offered differs from the specifications such difference must be explained in detail on sheets attached to the proposal and if such deviations do not depart from the intent of this notice and are in the best interest of the Town of Lewisboro the proposal will receive careful consideration.

3. ACCEPTANCE OR REJECTION

The Superintendent of Highways reserves the right to reject any or all bids, to accept any bid or waive any informality in the proposal as deemed advisable in the best interest of the Town of Lewisboro.

SPECIFICATIONS FOR CATCH BASINS, CATCH BASIN TOPS, & GRATE RISERS

Reinforced Precast 3 Foot Catch Basin		\$
Length Width Height Height Knockouts Walls Floor	56" 45" 36" (outside) 30" (inside) 24" (Min. on four sides) height of knockout above floor sump 9" 6" Thick (minimum) 6" Thick (minimum)	
Reinforced Precast	4 Foot Catch Basin	\$
Length Width Height Height Knockouts	56" 45" 48" (outside) 42" (inside) 31"(Min. on four sides) height of knockout above	e floor of sump 9"
Reinforced Precast Catch Baby Basin		\$
Length Width Height	32" 32" 24"	
Precast Reinforced		
Flat Top 45"	x 56"x 8" with Grate and Frame 19-1/2"x36"	\$
Curb Top 45"	x 56"	
11" thick at fr 8" thick at low 16" thick at co 19-1/2" x 36"		\$
Steel Grate Risers		
36" x 19.375 x 1.5" r	ise 3" thick	\$
20 1/8 x 19 5/8 x 2 5/ 19 ³ / ₄ x 19/ ¹ / ₂ x 2 5/8 1.5" rise		\$

Small variations from above dimensions will be considered if accompanied by complete specifications and detailed drawing and, if in the opinion of the Superintendent of Highways, the variations will not affect the structure stability or normal use of the item.

Prices quoted to be with delivery to the Lewisboro Highway Department Garage.

SPECIFICATIONS FOR CATCH BASINS, CATCH BASIN TOPS, & GRATE RISERS

Bidder's plant is located at	n, New York. Bidder certifies that plant	
Seal of Corporation	Legal name of Firm, Person, or Corpo	ration:
	Business Address:	
By:	Signature:	-
	Title:	

GUIDE RAIL AND POST INSTALLATIONS

Guide Rail and Post Installation Meeting Galvanized Specifications

1.	Complete layout and installation of guide rail and posts per New York state specifications	PER LINEAL FT
2.	Corrugated beam type guide railpunched 6'3"	PER LINEAL FT
3.	Corrugated beam type guide railpunched 6'3" curved to 50" radius and up	EACH
	curved 40 to 50' radius	EACH
	curved 30 to 39' radius	EACH
	curved 20 to 29' radius	EACH
4.	Corrugated beam type guide raillength 13'6.5" (shop curved rail)(approach and terminal) (rotation 90 degrees)	EACH
5.	3" x 2 3/8" I-intermediate guide rail postslength 5'3"	EACH
6.	Flared type terminal sections, 12 gauge	EACH
7.	Wrap around type terminal sections, 12 gauge	EACH
8.	Concrete anchor unit with all necessary hardware	EACH
9.	Galvanized splice bolts 1 1/4" x 5/8"	EACH
10.	Galvanized post bolts 5/16" x 1 3/4" with washer and nuts	EACH
11.	Galvanized post bolts 2' x 5/8"	EACH
12.	Galvanized support bolts 1/2" x 1 1/2", 2 nuts, no washers	EACH_

TOWN OF LEWISBORO GUIDE RAIL AND POST INSTALLATION

13.	6" x 6" x 24' box beam type guide rail, including shelf angle, splice plates, nuts, and bolts	PER LINEAL FOOT
14.	6" X 6" box beam type guide rail curved to special radius	PER LINEAL FOOT
15.	6" X 6" box beam type guide rail, shop cuts, and mitered curved rail	PER LINEAL FOOT
16.	6" x 6" box beam guide rail end sections	EACH
17.	3" I-beam guide rail posts 5' 3" long, intermediate type post for box beam rail	EACH
18.	3" I-beam guide rail posts 3' 8" long end type post for box beam rail	EACH

Detailed Specifications Timber Guide Rail For Roadside Projects and Maintenance

The Town of Lewisboro solicits bids for vendors to furnish and install at specified sites, Timber or Timberclad quiderail systems, for public roadsides and bridges, meeting applicable State and Federal Standards.

GENERAL NOTES

The Department seeks a unit <u>per foot</u> to supply all labor, materials, and equipment necessary to complete the work in compliance with Section 597 M of the *Standard Specifications for Construction and Materials* of the New York State Department of Transportation dated January 2, 1995 and addenda, or as detailed by these specifications.

DESCRIPTION OF ITEM

Roadside Timber Guide rail is to be installed to the lines and grades given in the project drawings and shall comply with the general requirements of Box Beam Type railing, as depicted in Standard Structure Sheets 606-3R4 and as modified herein.

The rail system shall consist of a 203 mm diameter round timber rail with a 6 mm thick steal C channel (60 mm by 121 mm) embedded into and bolted to the timber rail. The composite rail shall be attached to 1600 mm long S3 x 5.7 steel posts set 965 mm into the soil and spaced 3000 mm on centers. Each post shall include a 203 mm by 610 mm soil plate. The above-ground section of each post shall be covered by a routed, 171 mm diameter timber post which functions like a standard guide rail block while providing an all-wood appearance to the barrier from the roadside of the installation. Nominal rail height must be 660 mm, with a maximum of 685 mm above mean ground surface. Rail sections shall be joined using an S bolt, 12 mm (114 mm by 585 mm) splice bar.

Rail elements shall be fabricated from pressure treated Douglas Fir with an Equal to 1,000 Ksi and a Modulus of Rupture of 7,100 Psi or greater. Wood posts shall be pressure treated Red Pine No. 2, with a Equal to 1,100 Psi and Fb equal to 675 Psi or greater. All steel shall conform to ASTM A36 and be Hot Dipped Galvanized per ASTM A123. All steel hardware shall conform to ASTM A307 and be galvanized per ASTM A153. All wood products shall be pressure treated in conformance with Section 708-31 or Section 708-31 of the *NYSDOT Standard Specifications*.

1)	nonwood galde fan, price per E.i. complete				
	A) 1' – 100 L.F.	\$			
	B) 100' and over	\$			
2)	End terminal, type 1 timber rail complete	\$	each		
3)	End terminal, type 11' timber rail complete	\$	each		
4)	Anchorage unit for ironwood guide rail, back slope	\$	each		

1) Ironwood guide rail price per I. F. complete

TOWN OF LEWISBORO GUIDE RAIL AND POST INSTALLATION

Bidder's plant is located at	and is within	_ miles of the Town of			
Lewisboro Highway Garage at South Salem, New York. Bidder certifies that plant and materials					
meet requirements and specifications set forth by the Town of Lewisboro.					
Seal of Corporation	Legal name of Firm, Person,	or Corporation:			
	Business Address:				
D	a:				
By:	Signature:				
	Title:				

SPECIFICATIONS FOR YELLOW & WHITE PAVEMENT MARKING

Reflectorized Yellow & White Pavement Marking Paint

Paint shall meet all NYSDOT specifications as set forth in Specification Reference: SPEC-359, dated December 4, 1989.

Paint shall be specifically designed for use as a traffic marking paint, latex solvent base, quick drying, or VOC for Westchester County, NY. Applied at 15 mils, 300, if per gallons, per 4-inch strip, drying time ten minutes or less. Glass spheres should be applied at a rate of eight pounds per gallon. All paint materials shall meet VOC requirements for New York State Application. Air temperature shall be 50 degrees, and rising.

GENERAL

Paint shall be applied with atomizing spray-type machine. Applied marking shall have a clean-cut edge, true and smooth alignment and a uniform thickness of 15 mils, plus or minus, 1 mil. Any obvious detours from a smooth flow of the lines during application as determined by the Town of Lewisboro, or its representative, shall be removed and repainted by the contractor at his own expense. Glass spheres shall be applied uniformly over and into the wet paint film at a rate of six pounds per gallon of paint. Bid price shall include the cost of all labor, materials, and equipment required to PERFORM the work to the approval of the Town of Lewisboro. Paint shall be applied by a truck-mounted spray machine, no walk-type machine shall be acceptable for long line work. Paint shall be applied at the specified rate of application. Truck cab must accommodate two persons, so as to allow driver of mobile paint truck, plus Town of Lewisboro employee to sit in cab of truck to direct driver as to the application of paint onto Town of Lewisboro roads.

EQUIPMENT

Shall paint a straight and true line. Shall be able to paint a minimum of 20 miles per day of double center lane line. Shall be able to apply all road patterns. Driver of mobile paint truck shall have a minimum of three years experience. The operator shall have a minimum of two years experience.

INSURANCE

A copy of the contractor's liability insurance policy is required to be submitted with the bid forms. Minimum amounts and limits as per contractor's liability insurance to be attached to bid proposal.

Unit Price Per Mile, Single Center Line	\$
Unit Price Per Mile Double Center Line	\$
Unit Price Per Mile, Single White Edge Line	\$
4 inch Wide Stop Lines, per stop line	\$
Cross Walks, per cross walk	\$

TOWN OF LEWISBORO YELLOW & WHITE PAVEMENT MARKING

Bidder's plant is located at	and is within	miles of the Town of		
Lewisboro Highway Garage at Sou	th Salem, New York. Bidder certification	ies that plant and materials		
meet requirements and specifications set forth by the Town of Lewisboro.				
Seal of Corporation	Legal name of Firm, Person	on, or Corporation:		
	Business Address:			
		 -		
By:	Signature:			
	Title			